

Dimensions of Fiber Optic Winding Tubes for Security Applications



Overview

Typical dimensions of thick-walled microducts (AD/ID) are 7/3.5mm, 10/6mm, 12/8mm, 14/10mm and 16/12mm. For the application, these are usually protected by one or more outer layers. IDIL Fibres Optiques proposes its customers to coil fibers in-house. Our know-how regarding fiber optic coil winding enables us to work in accordance with customers' requirements. We provide optical fibers and then put them on the most appropriate stands whatever the material they are made of is. ion titled "01-SDMS-01, Rev 01" which shall be considered as an integra applicable for the equipment/material covered in this Distribution Material Standard Specification. In case of any conflict, the vendor/manufacture may propose equipment/material conforming to one group of industry codes. Fiber optic technology is the backbone of modern communication, enabling high-speed internet, telecommunications, and data transmission across vast distances. Uninterrupted monitoring of large infrastructure for increased safety and targeted preventative maintenance.



Article Content

Jun 14, 2026

Guide to Selecting the Best Conduit for Your Fiber Optic Project

How Do I Calculate the Proper Size for Fiber Optic Conduit? To calculate the proper size for fiber optic conduit, you need to consider the total diameter of the cables being used, as well as the conduit fill ratio.

Apr 27, 2026

Fiber Optic Cable Protection Tubes | Get A Quote | AerosUSA

We offer a wide range of protective conduits, in a variety of materials, to meet the needs of your application. Our conduits for fiber optic cables see use in opto-electronic instruments for the medical, ...

May 11, 2026

5 Key Factors for Choosing Fiber Optic Conduit Size

Discover the ideal fiber optic conduit size for your project. Our guide explains why choosing the right fiber optic conduit is crucial. Get detailed help now.

May 24, 2026

Fiberglass Tubes & Pipe | Filament Winding Fiberglass Tube

We custom fiberglass tubes in a variety of diameters, lengths, and wall thicknesses. Made by roll wrapping, pultrusion or filament winding.

Jan 26, 2026

13-SDMS-04 REV. 00 SPECIFICATIONS FOR NON-METALLIC, ...

The aim of this document is to provide generic information on design & construction of Non-Metallic Fiber Optic Cable (duct type & "mini cable" blown type) with loose tube, to be used for Outdoor ...

Sep 13, 2025

Microducts | Microtubes & composites for all applications

Thick-walled microducts have a solid wall thickness and are robust enough to protect the fiber optic cables running inside. Typical dimensions of thick-walled microducts (AD/ID) are 7/3.5mm, 10/6mm, ...

Aug 23, 2025

Finding the Right Size Innerduct Conduit for Fiber Optic Cable

Knowing the outer diameter of the cables you're installing is essential to choosing the right innerduct size. CablesPlus offers six sizes of fiber innerduct – $\frac{3}{4}$ inch, 1 inch, 1 $\frac{1}{4}$ inch, 1 $\frac{1}{2}$ inch, ...

Apr 22, 2026

Epoxy Fiberglass Winding Tube 360

Epoxy Fiberglass Filament Winding Tube is made of fiber glass yarn impregnated with insulation glue, epoxy resin and other resins by certain proportion, and then it is rolled in wet method, dried and ...

Oct 27, 2025

Duct Installation of Fiber Optic Cable

Fiber optic cable should not be coiled in a continuous direction except for lengths of 100 ft (30 m) or less. The preferred size for the figure-eight coil is about 15 ft (4.5 m) in length, with each loop 5 ft (1.5 m) ...

Jan 24, 2026

FIBER OPTIC COIL WINDING

Otherwise, a wide range of optical fibers types (single-mode, multi-mode, PM, from UV to IR) and dimensions are available, as well as coating materials (polymer, polyimide).

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://ntmmgroup.co.za>

Email: sales@ntmmgroup.co.za

Phone: +27 82 471 2596

Address: Unit 7, Optic Park, 24 High-Tech Lane, Century City, Cape Town, 7441, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

