

# Swiss Price Guaranteed Polarization Fiber 2-Core



## Overview

This high-performance Polarization Maintaining (PM) Fiber Patch Cord is engineered for precision-critical optical systems., photonic crystal, double clad, and rare-earth doped) fiber. Choose from FC/PC, FC/APC, or SMA connectors. For use in the mid-IR. DIAMOND PS+ is our most advanced high power fiber optic connector interface, designed to handle up to 16W optical power on single mode fibers. Built with Graded Index Fibers (GIF) for superior beam expansion and optical performance, PS+ offers lower insertion and return loss compared to ball. Polarization-maintaining (PM) fibers are single-mode optical fibers that possess a high built-in birefringence, distinguishing them from standard single-mode fibers where birefringence is minimized but random. This strong birefringence defines two orthogonal principal axes — typically called the. To tune the fiber for your application, changing the length of the fiber and/or the coil diameter, can alter the central wavelength and operating bandwidth. For more information and to discuss your precise requirements, contact us at [sales@fibercore](mailto:sales@fibercore).



## Article Content

Oct 21, 2025

### Optical Fiber & Fiber Patch Cables

Thorlabs manufactures and stocks a range of optical fibers and patch cables based on single mode (SM), polarization maintaining (PM), multimode (MM), or specialty (e.g., photonic crystal, double ...

Apr 25, 2026

### Polarization-maintaining Fibers – Buying Guide & Supplier List | RP ...

This polarization-maintaining fibers buying guide provides technical background, comparison of major types, selection criteria, and an overview of suppliers.

Feb 14, 2026

### Polarization Maintaining Fiber Cables | PM Fiber Cables

Polarization-maintaining, single-mode fiber cable with Gaussian intensity distribution and low-stress fiber connectors. Cut-off wavelengths from 360 nm to 1550 nm

Jul 15, 2026

### 2 Core Optical Fiber Cable\_Specification

Specifications are correct at time of printing and subject to change or alteration without notice.

Nov 28, 2025

### Fiber Optic Solutions for High-Performance | Diamond SA

Built with Graded Index Fibers (GIF) for superior beam expansion and optical performance, PS+ offers lower insertion and return loss compared to ball lenses. For maximum safety and reliability, it's ...

Apr 30, 2026

### POLARIZATION MAINTAINING FIBER PATCHCORDS AND ...

A client has a polarization maintaining fiber with normally an 80 micron cladding diameter, but the actual size can vary from 80 to 82 microns. He wishes to terminate the fibers with Ultra FC/PC connections.

Mar 20, 2026

### Fiber Arrays | Broadex Technologies

Broadex Technologies Fiber Arrays are assembled with high precision V groove arrays and undergo a unique assembly and polish process to obtain an extremely accurate fiber core position with ultra fine ...

Jan 20, 2026

Customized Polarization Maintaining Patch Cord – FC, LC, MPO

This high-performance Polarization Maintaining (PM) Fiber Patch Cord is engineered for precision-critical optical systems. Using Panda-type PM fibers and carefully aligned connectors, it ...

Dec 27, 2025

Zing™ Polarizing Fiber | Fibercore

To tune the fiber for your application, changing the length of the fiber and/or the coil diameter, can alter the central wavelength and operating bandwidth. For more information and to discuss your precise ...

Jun 03, 2026

Polarization Maintaining Fiber (PM Fiber) | OEM Optical ...

PANDA Polarization Maintaining (PM) fibers are designed with high performance properties including excellent birefringence and low attenuation. Corning offers the broadest portfolio of PANDA PM fibers ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://ntmmgroup.co.za>

Email: [sales@ntmmgroup.co.za](mailto:sales@ntmmgroup.co.za)

Phone: +27 82 471 2596

Address: Unit 7, Optic Park, 24 High-Tech Lane, Century City, Cape Town, 7441, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

